



# Weightrack



**M/s. WEIGHTRACK INDIA PVT. LTD.** is an ISO 9001:2015 Company. We manufactured world class products to meet our all-customer needs with commitment. Our Company is established in 1999 for manufacturing, sales and service supports of Weighing solutions, Weighing instruments, Industrial Weighing automation, Solar system along with Industrial automation logistics management system, Automatic traffic management system and Toll management system. We are a family of more than 4000 happy clients, which is a motivational number for us to keep up with meeting quality commitment.



PLOT NO. 623 (P), HANSPAL (NEAR PURI CANAL)  
BHUBANESWAR-752101, ODISHA,

0674-2463002, 9040077885

SALES@WEIGHTRACKINDIA.COM

WWW.WEIGHTRACKINDIA.COM

# **BATCH /HOPPER/TANK/SILO WEIGHING CONTROLLER-G800E**



## **Description**

➡ Batch /Hopper/Tank/Silo is state of the art industrial controller. "G800E" find its utility in industrial automation applications. It takes weight based input from load cells and generates control using potential free relay outputs. It is having provision to connect external proximity switches for external controls or interlocking the process

## **Hardware Features**

- 32-bit ARM processor
- Sigma Delta type 24 bit ADC
- Two Seven Segment LED displays for weight, process indication
- SMPS power supply
- 16key front mount keyboard
- 6 potential free relay outputs with isolation and electrical noise immunity.
- 5 digital inputs (DI) for connecting external switches/sensors
- RS232 port for continuous transmission of current weight
- Tabletop port for connecting external wired displays.
- Panel mount industrial housing.
- Analog output 4-20mA , 0-10V (OPTIONAL)

## **Software Features**

- Password protected Installation settings
- 3 step software calibration Multi step Smart Calibration
- Zero, weight tracking feature.
- Vibration control features.
- Self-test for display / relay / DI's
- Factory set Logic of operation, customized as per need.
- Manual inflight correction
- Counter, totalizer
- Auto / Manual mode of working (OPTIONAL)
- Auto inflight correction (OPTIONAL)
- RS485 communication / Modbus protocol (OPTIONAL)

## **Salient features**

G800E can be made available for any of the following field requirement

- Feeding of a material precisely using coarse-fine arrangement
- Feeding of more than one materials
- Discharge of a ready batch from weigh hopper
- Dispensing required quantity from weigh hopper o Check weighing
- Automatic Bag filling considering precise quantity and clamping action.
- Tank Level maintaining and many more....

0674-2463002, 9040077885 

SALES@WEIGHTRACKINDIA.COM 

WWW.WEIGHTRACKINDIA.COM 



PLOT NO. 623 (P), HANSPAL (NEAR PURI CANAL) BHUBANESWAR-752101, ODISHA,

## Specification

➤ Processor	32 bit ARM processor
➤ Processor Clock	50 MHz.
➤ Display	Two numbers 6-digit red 7-segment LED display
➤ Power Supply	SMPS type EMI/RFI filter with spike suppressor
➤ Fuse	Fuse 750mA for AC power in
➤ Input Voltage	90V to 270V AC @ 50Hz
➤ Protection	RFI/EMI filter for input power, Spike suppressor for input transients.
➤ Indication	Buzzer for fault indicaton and data entry
➤ Output	6 inbuilt potential free relay output for driving solenoid valves/contractor switches.
➤ Digital Input	5 Digital input for connecting remote switches OR other interlocking signals.
➤ Remote Display Port	9-pin D-shell female connector for optional ½"/ 1"/2.3"/ 4" 6-digit bright red LED display.
➤ Serial Port	RS-232C port for computer interface or remote display interface.
➤ Keypad	16-key front mount keypad for data & function entries.
➤ A/D Converter Resolution	Sigma Delta Type with 24 bits resolution
➤ Conversion Speed	50 Hz
➤ Load Cell Excitation	8V @ 300mA (up to eight load cells of 480 ohms each).
➤ Input Signal	1 to 3 μV per division of weight
➤ Power Consumption	10VA (approx)
➤ Environment	Operating Temp - 0 o to 55o C, Humidity - upto 95% RH non condensing
➤ Mechanical	Industrial panel mounting enclosure with sheet metal and extruded alummium section. Case size: 184 x 90 x 198 mm(W) (L) (H) Bezel size : 190x96 mm Panel cut out : 184X90 mm Depth : 220 mm with rear panel connector weight: 2.2Kg



0674-2463002, 9040077885 

SALES@WEIGHTRACKINDIA.COM 

WWW.WEIGHTRACKINDIA.COM 



PLOT NO. 623 (P), HANSPAL (NEAR PURI CANAL) BHUBANESWAR-752101, ODISHA,

# OUR CUSTOMERS



## ALL BRANCHES

| NEW DELHI | | HYDERABAD | | KOLKATA | | RANCHI | | INDORE | | JHARSUGUDA | | BARBIL |



PLOT NO. 623 (P), HANSPAL (NEAR PURI CANAL)  
BHUBANESWAR-752101, ODISHA,

0674-2463002, 9040077885

SALES@WEIGHTRACKINDIA.COM

WWW.WEIGHTRACKINDIA.COM